

29L-V/45L-V (LED) Table Type Pulse Vacuum Steam Sterilizer (Touch Screen)



Characteristics

- Touch screen.
- Suitable for different types instruments: Surgical instruments, dental instruments, glass wares, injection units and other objects of compression resistance and hot steam resistance.
- Double lock system- mechanical lock with air lock system.
- Six layer's new structure chamber, creating new chamber structure:
 1. The chamber adopts six layers' structure, using the special shaping finish drawing technology, dusting and polishing. It has super-strong pressure-bearing properties, and pass 60000 times fatigue life testing, the outer layer adopts the superfine micropore foaming technique.
 2. As the tray rack can rotates to 90 degrees, 5 trays can be used for placing instruments.
- Two condensers, faster cooling, prolongs life time.
- Safety valve: release pressure overload, and restores idle chamber pressure when the chamber is over-pressured.
- Air filter: filter airborne impurities into the chamber to prevent contamination.
- Big capacity open tank:
 1. Open tank, easy-to-clean.
 2. Built-in water quality sensor monitors water quality, reduces machine failure rate, and prolongs machine life time.
- Two types of record (dual recording)
 1. USB Master controller stores 2,000 fresh cycles; the data can be downloaded via USB. You can check and print all the records with a computer.
 2. Micro-Printer (Optional) Prints cycle data when the cycle ends.

Technical Specifications

PARAMETER	29L-V	45L-V
Voltage (V/Hz)	230/50	230/50
Power (W)	3300	3300
Capacity (L)	29	45
Chamber size (mm)	Ø319×420	Ø319×620
Product size (mm)	535x650x505	535x850x505
N. W (KG)	80	92