

FEC-6000B Portable USB Video Gastroscope/ Colonoscope

(Used for Bovine and Horse)



Features

- The multifunctional Gastroscope using polycarbonate new composite handle, reasonable designed the clamp hole position, the washable pipe system can protect the lumen unobstructed, to prevent the pipeline blockage, with biopsy forceps hole to ensure the pliers and other devices unobstructed. When do surgery, the suction valve is convenient, removable, safe and reliable, so that users do not feel fatigue in the operation.
- The excellent operation of the traction device can be easily transfer and adjust the bending parts to upward, downward. Can smoothly and fastly reach to the desired site of observation. And timely and accurate detection of diseased tissue.
- The scope with multi-coated high transmittance imaging system, round field of view, wide viewing angle, wide field of view, the scene is broad and wide, 3-100 mm range can see more clear picture, so that the observation and diagnosis correctness greatly improved.
- The high-definition CMOS camera makes users to get clearer, wide and bright image.

Technical Specifications

Website: www.hqs-vetcare.com

Add: Room 402, Unit 6, Building 27, Pingchou District 2, Jiangdong Street,
Yiwu, Jinhua, Zhejiang Province

PARAMETER	SPECIFICATION
View of field	140°
Diameter of distal-end	Φ12.8mm
Outer diameter of insert tube	Φ12.8mm
Depth of view	3-100mm
Working length	3000mm
Working channel	Φ3.2mm
LCD	Use computer LCD
Image solution	CMOS 1,000,000 pixels
Bending range	Up 180°, Down 90°, L/R 100°

Parts List

PRODUCT NAME	UNIT	QUANTITY
Portable Gastroscope	set	1
Biopsy forceps	set	6
Cleaning brush	set	1
Leak detector	set	1
Attract valve anti jet cover	set	2
Endoscope case	set	1
Mini pump (Portable)	set	1
Charge	set	1
User manual	pc	1
Certificate	pc	1

Optional

PRODUCT NAME	PICTURE	SPECIFICATIONS
--------------	---------	----------------

Laptop computer		HUAWEI MateBook D 14 SE
Light cold source machine		1. Voltage: 220V-240V 2. Frequency: 50-60HZ 3. Lamp Power: 15V-150W environmentally friendly halogen tungsten lamp 4. Illumination: 70000LX (using special measuring tools) 5. Color Temperature: 3000~7000K 6. Air Pump Pressure: 30-60kpa 7. Air Flow: 4L/min-10L/min (Quiet pump)
Trolley		