

HC-16A

High Speed Centrifuge



Specifications

- Time: 0-99min
- Max RCF: 17000xg
- Max RPM: 16000RPM, stepless speed adjustment
- Rotor capacity: 1.5/2ml*12 (Standard Rotor 1)
- Voltage: 110V 60Hz/220V 50Hz
- Dimension: 410*520*320mm; Weight: 27kg
- Strong metal case, stainless steel chamber
- Brushless motor, LED display speed, RCF and time
- Available different rotors
- Over speed and imbalance alarm
- Rotor identification, electromagnetic door locks
- Touch panel control, the error code display
- Suitable for experiments of biology, pharmacology and agriculture
- For researches on genes and protein nucleic acid
- LCD display optional

Optional Rotors

MODEL	MAX SPEED	ROTOR CAPACITY	MAX RCF
Rotor 1	16000 r/min	1.5/2ml*12	17800xg
Rotor 2	13500 r/min	1.5/2ml*24	15100xg
Rotor 3	12000 r/min	10ml*12	14800xg
Rotor 4	13000 r/min	5ml*8	11400xg
Rotor 5	11000 r/min	50ml*6	12000xg
Rotor 6	13500 r/min	0.5ml*48	14800xg
Rotor 7	13000 r/min	1.5ml*36	14500xg
Rotor 8	10000 r/min	100ml*4	9800xg