

# HWP-II

## Water Purifier



### Specifications

| MODEL                    |                        | HWP-II 15                                                          | HWP-II 30            |
|--------------------------|------------------------|--------------------------------------------------------------------|----------------------|
| Water Output Type        |                        | RO Water                                                           |                      |
| Water Output Speed       |                        | 15L/H                                                              | 30L/H                |
| Purifying Procedure      |                        | PF+AC+RO+AC                                                        |                      |
| Water Supply Requirement |                        | Tap water:TDS<200 ppm,5~45°C,1.0-4.0kg/c                           |                      |
| Purification system      | Pretreatment unit      | PP filter×1 + PP cotton filter×1<br>Special active carbon filter×2 |                      |
|                          | RO unit                | 100GPD RO membrane×1                                               | 200GPD RO membrane×1 |
| Pure water quality       | Ion rejection rate     | 97%~99% (New RO membrane)                                          |                      |
|                          | Organic rejection rate | 99%,when MW > 200 Dalton                                           |                      |

|                        |                         |                                                                                                      |
|------------------------|-------------------------|------------------------------------------------------------------------------------------------------|
|                        | Bacteria                | <0.1cfu (with optional 0.45+0.1 μm PES terminal filter)                                              |
|                        | Particles<br>( > 0.2μm) | -                                                                                                    |
| Flow rate              |                         | 2 Liters/min (with pressure tank)                                                                    |
| Water quality monitor  |                         | TDS/conductivity test pen                                                                            |
| Consumption            |                         | 72W                                                                                                  |
| Power supply           |                         | AC220V,50/60Hz(Standard);AC110V,60HZ(Optional)                                                       |
| External Size (H×W×D)  |                         | 410*220*420mm                                                                                        |
| Package Size (H×W×D)   |                         | 600*490*580mm                                                                                        |
| Weight                 |                         | 35kg                                                                                                 |
| Standard configuration |                         | Main body (including: 1 set cartridge) + 15 liters tank + TDS/conductivity test pen + accessory pack |