

HWP-IV Water Purifier



Features

- Large LED display, show all the running state and parameters.
- RO membrane clean automatically. High/Low pressure protection.
- Alarm function: Water quality, no water, full water, consumables life ending. Automatic diagnosis.

Specifications

MODEL		HWP-IV 45	HWP-IV 63	HWP-IV 94	HWP-IV 125
Water Output Type		RO water			
Water Output Speed		45L/H	63L/H	94L/H	125L/H
Flow procedure		PF+AC+AC+RO			
Water Supply Requirement		Tap water: TDS<200 ppm, 5~45°C, 1.0-4.0Kgf/cm ² (if TDS>200ppm, extra pretreatment filter is recommended)			
Purification system	Pretreatment unit	20" PP filter×1+20" granular active carbon filter×1+20" active carbon block filter×1			
	RO unit	300 GPD RO membrane×1	400 GPD RO membrane×1	600 GPD RO membrane×1	400 GPD RO membrane×2
Pure water quality	Ion rejection rate	97%~99% (New RO membrane)			

Website: www.hqs-vetcare.com

Add: Room 402, Unit 6, Building 27, Pingchou District 2, Jiangdong Street,
Yiwu, Jinhua, Zhejiang Province

	Organic rejection rate	> 99%,when MW > 200 Dalton	
	Particles and bacteria		
	Rejection rate	>99%	
	Bacteria	<0.01cfu/ml (with optional 0.2μm PES terminal filter)	
	Particles(> 0.2μm)	<1/ml (with optional 0.2μm PES terminal filter)	
Water Quality Monitor		TDS/conductivity test pen	
Consumption		120W	240W
Power supply		AC220V,50/60Hz(Standard);AC110V,60HZ(Optional)	
External Size (H×W×D)		640*540*1110mm	
Package size (H×W×D)		650*750*1280mm	
Weight		90kg	
Standard configuration		Main body (include 1 set of purification column) + 2 built-in15L water tank + TDS/conductivity test pen + accessory pack	