

LC-06F (Table) Refrigerated Centrifuge



Product Characteristics

- Refrigerated centrifuge is melt housing, safe & compact
- Microprocessor control, less noise and fast cooling
- Brush-less frequency motor, free maintenance, no powder pollution, quick in speed up and down.
- The flexible axle driven system which drive the rotor directly, smooth in operation and small vibration.
- Many rotors for choice, suitable for different specifications meets customers' different requirements of separation.
- Digital display the speed, time and RCF.
- Auto-electric lid lock, over-speed protection.

Specifications

Max speed: 5000rpm
Speed accuracy: ± 20 rpm
Max RCF: 4730 $\times$ g
Timer: 99h59min
Max volume: 4 $\times$ 800ml
Temperature range: -20 $^{\circ}$ C ~40 $^{\circ}$ C
Power supply: 220V 50HZ
Dimension(mm): 700 $\times$ 715 $\times$ 420
Weight: 130kg

Optional Rotors

Rotor 1: 10/15ml*12 angle rotor
Rotor 2: 750ml*4
Rotor 3: 500ml*4
Rotor 4: 250ml*4
Rotor 5: 500ml (blood bag) *4
Rotor 6: 500ml*6
Rotor 7: 5ml*72
Rotor 8: 7ml*148/108
Rotor 9: 96 holes*2*2
Rotor 10: 50ml*8
Rotor 11: 10/15ml*32
Rotor 12: 15ml*16
Rotor 13: 100ml*4
Rotor 14: 100ml*8