

LX-D Digital Vertical Pressure Steam Sterilizer



Features

- Full SUS 304 stainless steel structure
- Accurate double scale indication pressure gauge
- Silicone seal ensuring no steam leakage
- Temperature and time of sterilization can be set
- Emergency stop switch
- Automatic release when overpressure
- Automatic power off when water shortage
- Drying function can be added
- PID Microcomputer Control, LED digital display temperature and time

Technical Specifications

Model	LX-D35L (Digital)	LX-D50L (Digital)	LX-D75L (Digital)	LX-D100L (Digital)	LX-D120L (Digital)	LX-D150L (Digital)
Volume	35L	50L	75L	100L	120L	150L
Max Working Temperature	134℃	134℃	134℃	134℃	134℃	134℃
Max Working Pressure	0.22Mpa	0.22Mpa	0.22Mpa	0.22Mpa	0.22Mpa	0.22Mpa
Time Range	0-999min	0-999min	0-999min	0-999min	0-999min	0-999min
Temperature Range	RT-134℃	RT-134℃	RT-134℃	RT-134℃	RT-134℃	RT-134℃
Sterilization Chamber	Φ320*485 mm	Φ320*545 mm	Φ388*480 mm	Φ388*630 mm	Φ460*590 mm	Φ460*700 mm
Power	AC220V/50 Hz/2.5KW	AC220V/50 Hz/2.5KW	AC220V/50 Hz/3.5KW	AC220V/50 Hz/4.0KW	AC220V/50 Hz/4.0KW	AC220V/50 Hz/4.0KW