

LX-H Digital & Hand shaking Pressure Steam Sterilizer

Features

- Full SUS 304 stainless steel
- LED digital display sterilization temperature and time
- Hand wheel quick open door
- Safety interlocking
- Automatic release when overpressure
- Automatic power off protection
- Tempered glass anti-scald protection
- Sound-light alarm when sterilization finished
- Drying function can be added
- PID Microcomputer Control heating, air release, temperature, time and steam release



Technical Specifications

Model	LX-H35L-I (Digital & hand shaking)	LX-H50L-I (Digital & hand shaking)	LX-H75L-I (Digital & hand shaking)	LX-H100L-I (Digital & hand shaking)
Volume	35L	50L	75L	100L
Max Working Temperature	134℃	134℃	134℃	134℃
Max Working Pressure	0.22Mpa	0.22Mpa	0.22Mpa	0.22Mpa
Time Range	0-9999min	0-9999min	0-9999min	0-9999min
Temperature Range	RT-134℃	RT-134℃	RT-134℃	RT-134℃
Sterilization Chamber	Φ320*420	Φ320*530	Φ388*480	Φ388*630mm
Power	AC220V/50Hz/2.5 KW	AC220V/50Hz/2.5 KW	AC220V/50Hz/3.5 KW	AC220V/50Hz/4.0 KW
Drying Temperature (Optional)	60-110℃	60-110℃	60-110℃	60-110℃