

RF-V226

Medical Pharmacy Refrigerator

(2~8°C)



Features

- Adjustable temperature range 2~8°C
- Microprocessor control, digital display, and temperature adjustment with an increment of 0.1°C
- Large digital display screen
- Temperature variation within $\pm 3^{\circ}\text{C}$
- Permanently lubricated cooling fan for safety and longevity
- High efficiency specialty compressor with known field reliability
- Forced- air cooling with optimized air distribution system designed

Safety

- Build-in back-up battery can display temperature and operate audible and visual alarm system for up to 48 hours without AC power.
- Visual and audible alarm system: High/low temperature, thermostat failure alarm, power failure alarm, door ajar.
- Power failure protection: turn on delay of the cooling system when power failure, restart delay protection.
- Keyboard lock, password protection to avoid set parameter randomly.
- Wide available voltage range: 187V~242V.

Humanized Design

- Optimized space utilization design with multi-level and adjustable shelf height to accommodate storage requirement of pharmaceutical products of various kinds.
- Standard with LED Interior light
- Safety lock to prevent unauthorized access

Technical Data

- Capacity: 226L
- Temperature range: 2~8°C
- Ambient temperature: 10~32°C
- Controller: Microprocessor
- Display: Digital display
- Compressor: 1
- Refrigerant: R600a
- Cooling type: Forced-air cooling
- Defrost type: Auto defrost
- Power supply: 220V~240V/ 50~60Hz; 115V/ 60Hz
- Rated power: 140W
- Electrical current: 1.0A
- Power consumption: 1.6kWh/24h

Accessories

- Caster: 4
- Lamp: LED
- Door: 1 (Glass door-LOWE)
- Shelf: 4
- Test hole: 1/25MM
- USB Port/Datalogger:Optional

Dimension

- Interior size (W*D*H): 534*406*1150mm
- Exterior size (W*D*H):625*594*1707mm
- Package size (W*D*H):707*676*1820mm
- NW/GW: 73/76kg
- Loading quantity (20'/40'/40'H): 24/51/51