

RF-V60G

Medical Pharmacy Refrigerator

(2~8°C)



Features

- Accurate temperature controller, ensure the inside temperature within 2~8°C and accuracy 0.1°C.
- Specially designed forced-air cooling system, circulating air cold back blowing technology, ensure frost-free cabinet and good temperature uniformity.
- Suggested ambient temperature 10~32°C.
- Double-layer hollow insulation LOW-E glass door, use light reflection to prevent condensation.
- Cold spray steel plate inner chamber for friendly using and easy cleaning.
- Wide available voltage range: 187V~242V.

Safety

- Keyboard locking, password protection function, to prevent unauthorized access adjustment of operating parameters
- Built-in backup battery to display temperature and to operate audible and visual alarm system for up to 8 hours without AC power
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening
- Visual and audible alarms: high/low temperature, power failure, thermostat failure, door ajar, 4 visual and audible alarms
- Power failure protection: turn on delay of the cooling system after power failure
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when controller or two sensors failed

Humanized Design

- 4 adjustable bottom foot design for easy adjustment of height and fixation
- 2 adjustable steel wire impregnated plastic shelf for easy storing
- Special designed service-free drainage system ensure no water in the cabinet
- Auto on/off LED light with manual switch on control panel
- LED digital display can display inside the machine temperature and alarm information
- 1 standard test hole for easy installation of temperature recorders

Technical Data

- Capacity: 60L
- Temperature range: 2~8℃
- Ambient temperature: 10~32℃
- Controller: Microprocessor
- Display: Digital display
- Compressor: 1
- Refrigerant: R600a
- Cooling type: Forced-air cooling
- Defrost type: Frost free
- Power supply: 220V 50~60Hz; 115V 60Hz
- Rated power: 72W
- Electrical current: 0.59A
- Power consumption: 0.84kWh/24h

Accessories

- Adjustable foot: 4
- Lamp: LED
- Shelf: 2
- Test hole: 1/25mm

Dimension

- Interior size (W*D*H): 410*315*560mm
- Exterior size (W*D*H): 495*450*710mm
- Package size (W*D*H): 558*510*760mm
- NW/GW: 33/37KGS
- Loading quantity (20'/40'/40'H): 132/276/276